

## **L3HARRIS SINGARS RT-1523**

### **VHF Radio**

The L3Harris SINGARS RT-1523 Combat Net Radio equips warfighters with robust, time-tested capabilities on the move.



The L3Harris RT-1523 is a ruggedized system delivering highly secure voice and data communications for superior Command and Control (C2). With flexible frequency selections and security options available from the front panel, it allows local units to effectively manage multiple operations.

This SINGARS VHF radio system is engineered to meet versatile mission

needs—as a manpack to soldiers at dismount, and on the move with the Vehicular Amplifier Adapter. In the mobile role, the radio works with the Embedded Tactical Data Router, and as a manpack, it features a standard Point-to-Point-Protocol interface. Both allow a C2 application to access the Tactical Internet.

The RT-1523 enhances warfighter safety and awareness with a Radio Based Combat Identification capability, which can perform in an interrogator or responder role on the ground or in the air. When combined with the available embedded Selective Availability Anti-spoofing Module (SAASM) GPS receiver option, it provides secure voice, data and position location reporting in a single system.



## **BATTLE-PROVEN COMBAT COMMUNICATIONS FOR IN-VEHICLE OR DISMOUNTED CONFIGURATIONS**

### **KEY BENEFITS**

- > **World's most-fielded radio technology**
- > **Versatile use for troops on the move or at the halt**
- > **Configuration options for enhanced Situational Awareness and Position Location Information**
- > **Gen 3 Night Vision Goggle display compatibility**

## RT-1523 CONFIGURATIONS



RT-1523 5 W manpack dismount configuration



RT-1523 in a VAA mount, vehicular 50 W long range/short range



RT-1523 in a VAA mount, 50 W dual long range (retransmit), plus 2nd power amp and retrans cable

GENERAL	
RT Nomenclature	RF-1523
Frequency Range	30.000-87.975 MHz
Channel Spacing/Bandwidth	25 kHz
Net Presets	8 Single Channel/6 Frequency Hopping
GPS	Optional SAASM

TRANSMITTER	
Power Output	1 mW, 100 mW, 5 W, 50 W (with power amplifier)
Antenna Outputs	1 (30.000-87.975 MHz)

POWER	
Power Input	12-14 Volt Battery/+28 Vdc per MIL-STD-1275
Battery Types	BA-5590, BB-2590, and BB-590

SECURITY	
Encryption	Internal Encryption Module
Encryption Modes	CT/PT

MODES AND WAVEFORMS	
Narrowband Waveforms	SINGGARS
Voice and Data Modes	Single-channel and frequency hopping MIL-STD-188-220C operations with Tactical Internet X.21 packet data interface RS-232 data at 1200, 2400, 4800 and 9600 bps Synchronous data at 1200, 2400, 4800 and 16000 bps
Transmission Modes	FM (digital or analog)

PHYSICAL	
Dimensions	3.4 H x 5.3 W x 10.15 D in (8.7 H x 13.4 W x 25.8 D cm)
Volume	181.42 in <sup>3</sup> (2973 cm <sup>3</sup> )
Weight	7.8 lbs (3.5 kg) with embedded battery

ENVIRONMENTAL	
Shock and Vibration	MIL-STD-810
Immersion	MIL-STD-810 to 1 Meter
Temperature	-58°F to +160°F (-50°C to +71°C)
EMI/RFI	MIL-STD-461
Sand/Dust/Salt Fog/Rain	MIL-STD-810
Humidity	MIL-STD-810

See L3Harris Product Catalog for accessories

### L3Harris SINGGARS RT-1523 VHF Radio

© 2019 L3Harris Technologies, Inc. | 09/2019 DS615

#### Non-Export Controlled Information

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



1025 W. NASA Boulevard  
Melbourne, FL 32919