

VRS7000 SERIES CROSS-BAND VEHICULAR REPEATER

700 MHz, 800 MHz

The P25 Vehicular Repeater is a public safety mobile radio system that embeds either an XG-75M single-band or Unity® XG-100P multi-band mobile, providing P25 digital trunked or conventional communications. In addition to performing all of L3Harris' mobile radio functions, the repeater provides network extension to portable radios that cannot directly connect to the P25 network.



EXTENDED COVERAGE

A portable that has moved out of range of the network can be connected to the Vehicular Repeater and normal call traffic can be established across the repeater to the network via the embedded highpower mobile radio.

In addition to supporting up to 64 users and up to 64 groups, the P25 Vehicular Repeater allows the following P25 functions across the RF links:

- > Portable Unit Identifiers
- > P25 Group Calls
- > P25 Individual Calls
- > P25 Emergency
- > P25 System All Call from the network
- > P25 System Grant and Call Queued Tones
- > Call Grant and Call Queued Tones
- > Request-to-Talk and Emergency Request-to-Talk

SCENE OF INCIDENT

The Scene-of-Incident (SOI) mode enables nearby P25 radios operating on the Vehicular Repeater frequency channel the ability to communicate with each other using the VRS7000 as a base station. Although this mode does not include a connection to the P25 network, the following functions are provided:

- > P25 Group Calls
- > P25 Individual Calls
- > P25 Emergency
- > Call Grant and Call Queued Tones

EXTENDED COVERAGE FOR ENHANCED CRITICAL COMMUNICATIONS

KEY BENEFITS

- > Extended connectivity for P25 trunked and conventional networks
- > Optional Advanced Encryption Standard (AES) encryption for end-to-end encryption across the repeater. Encryption is maintained from the portable through the repeater to the network, providing secure communications
- > Scene of incident local repeat capability
- > Provides digital interoperability with other P25 users during critical communications situations



GENERAL SPECIFICATIONS	
Dimensions (H x W x D)	Repeater (VRB) only 8 x 8 x 9 in (203 x 203 x 229 mm)
Ambient Temperature Range	-22° to +140°F (-30° to +60°C)
Storage Temperature Range	-40° to +185°F (-40° to +85°C)
Input Voltage	13.8 ± 10% VDC
Input Current	4A Rx mode 15A Tx mode at full power
For full specifications on the mobile radio unit, refer to the Unity XG-100M or XG-75M data sheet	

ENVIRONMENTAL SPECIFICATIONS		
Standard	Parameter	Methods & Procedures
MIL-STD-810E*	Low Pressure	500.3 PI, PII
	High Temperature	501.3 PI, PII
	Low Temperature	502.3 PI, PII
	Temperature Shock	503.3 PI
	Solar Radiation	505.3 PII
	Blowing Rain	506.3 PI
	Humidity	507.3 PII
	Salt Fog	509.3 PI
	Blowing Dust	510.3 PI
	Min Integritiy Vibration	514.4 PI, Cat. 10
	Functional/Basic Shock	516.4 PI
	Transit Drop	516.4 PII
TIA/EIA-603-A	Vibration Stability	Par 2.3.4 & 4.3.4
	Shock Stability	Par 2.3.5 & 3.3.5
U.S. Forest Service	Vibration Stability	Par 7.15
*Also meets equivalent superseded MIL-STD-810C and -D		

REGULATORY DATA							
Vehicular Repeater Model Number	Frequency Range (MHz)	RF Output (W)	Frequency Stability (ppm)	FCC Type Acceptance Number	Applicable FCC Rules	Industry Canada Certification Number	Applicable Industry Canada Rules
VRBS7010	764-767 769-771	4	1.5	OWDTR-0058-E	90	3636B-0058 single	RSS-119
VRBS7020	856-869	4	1.5	OWDTR-0058-E	90	3636B-0058 single	RSS-119
VRBS7030	764-776 851-869	4	1.5	OWDTR-0058-E	90	3636B-0058 single	RSS-119

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

TRANSMITTER			
	VRS7010	VRS7020	VRS7030
Frequency Band (MHz)	700	800	700/800
Tx Frequency Range (MHz)	764-767, 769-771	856-869	764-776, 851-869
Rx Frequency Range (MHz)	794-797, 799-801	811-825	794-825
Rx to Tx Frequency Offset (MHz)	30	45	-20
Channel Spacing (kHz)	12.5	12.5	12.5
Transmit Output Power (Configurable Range) (W)	0.25 to 4	0.25 to 4	0.25 to 4

VRS7000 Series Cross-Band Vehicular Repeater

© 2020 L3Harris Technologies, Inc. | 04/2020 DS1726

Non-Export Controlled Information

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



1025 W. NASA Boulevard
Melbourne, FL 32919