



L3HARRIS™
FAST. FORWARD.

ONYX COMPACT MID-WAVE INFRARED SENSORS

Micro SD/HD, SD/HD

	ONYX MICRO SD	ONYX MICRO HD
Camera System Parameters		
Sensor Type	HOT MWIR, reticulated FPA	HOT MWIR, reticulated FPA
Sensor Size	640 x 512 pixels, 15 µm pitch	1280 x 720 pixels, 8 µm pitch
Spectral Band	MWIR	MWIR
f/#	4.0 std, options for 2.3 and higher	2.3 (Other f/#s available)
System Control	RS-422 serial interface (115.2 kbps)	RS-422 serial interface (115.2 kbps)
Video Format	NTSC/PAL SDI and serial differential CameraLink®	CameraLink® HD-SDI
Cooler	Linear closed-cycle Stirling	Linear closed-cycle Stirling
Power Requirements		
Power Source	+12 VDC and +5 VDC	+12 VDC and +5 VDC
Operating	< 9 W typical at 23 °C	< 8 W typical at 25 °C
Cool-Down at 23 °C	< 16 W	< 16 W
Mechanical/Environmental		
Weight	< 0.9 lb	< 0.9 lb
Size	3.0" L x 2.0" W x 2.9" H including cooler electronics	3.0" L x 2.0" W x 2.9" H including cooler electronics
Operating Temperature	-40 °C to +70 °C	-32 °C to +70 °C
Storage Temperature	-40 °C to +85 °C	-40 °C to +85 °C
Typical Performance		
Cool-Down Time at 23 °C	< 6 minutes	< 6 minutes
Operability	> 99.5% of pixels	> 99.4% of pixels
	ONYX SD	ONYX HD
Camera System Parameters		
Sensor Type	HOT MWIR, reticulated FPA	HOT MWIR, reticulated FPA
Sensor Size	640 x 512 pixels, 15 µm pitch	1280 x 720 pixels, 8 µm pitch
Spectral Band	MWIR	MWIR
f/#	4.0 std, options for 2.3 and higher	2.3
System Control	RS-422 serial interface (115.2 kbps)	RS-422 serial interface (115.2 kbps)
Video Format	NTSC/PAL SDI and serial differential CameraLink®	CameraLink® HD-SDI
Cooler	Linear closed-cycle Stirling	Linear closed-cycle Stirling
Power Requirements		
Power Source	+12 VDC	+12 VDC and +5 VDC
Operating	< 9 W typical at 23 °C	< 10 W typical at 25 °C
Cool-Down at 23 °C	< 20 W	< 20 W
Mechanical/Environmental		
Weight	< 2.75 lb	< 2.75 lb
Size	4.8" L x 3.3" W x 3.5" H including cooler electronics	4.8" L x 3.3" W x 3.5" H including cooler electronics
Operating Temperature	-40 °C to +70 °C	-40 °C to +70 °C
Storage Temperature	-40 °C to +85 °C	-40 °C to +85 °C
Typical Performance		
Cool-Down Time at 23 °C	< 6 minutes	< 6 minutes
Operability	> 99.5% of pixels	> 99.4% of pixels



Low size, weight and power (SWaP) and great video in one camera, the Onyx models are some of the smallest high-resolution mid-wave infrared (MWIR) cooled cameras in the world. Based on our high-operating temperature (HOT) MWIR focal plane array (FPA) technology, these high-performance camera cores deliver superior imaging quality and are ideally suited for SWaP-sensitive air, sea and land applications. These units have been designed for easy integration into a variety of applications, including electro-optical payloads, weapon sights, hand-held viewers, remote weapon stations and enhanced vision systems. The cameras consist of integrated detector/dewar cooler assemblies and camera electronics combined with our patented image enhancement processing.

Onyx provides a full range of video processing options which allow use of a common module in multiple platforms. The Onyx features local area contrast enhancement, proprietary detail and enhancement algorithm, interpolated electronic zoom up to 4x, 3- or 5-point non-uniformity correction (NUC), autofocus, edge enhancement, adaptive temporal noise reduction, 30 or 60 hertz operation and integration time adjustment. Also included are selectable region of interest for AGLC and ALC, lens control, image polarity (white or black hot), muzzle flash suppression, manual gain and level control, video freeze, video orientation, up to eight selectable dynamic ranges, scene-based NUC, electronic image stabilization and turbulence mitigation. The system also provides built-in test and on-board temperature sensors.



ONYX MICRO

At less than 0.9 lb and with low power consumption, our Onyx Micro is the perfect high-performance, miniature camera for small SWaP platforms. Small element pixel pitch enables miniaturization of the assembly and optics. L3Harris' image enhancement processing delivers exceptional image quality in all scenes and features automatic gain control and NUC. High-operating temperature MWIR FPA technology enables an ultra-small cryocooler. Patented reticulated pixels eliminate FPA "cross talk" resulting in an exceptionally crisp infrared image. Steady-state power consumption is less than eight watts. L3Harris' proven technology enables high sensor reliability and significantly lowers total life cycle costs.

Compact Mid-Wave Infrared Sensors

© 2021 L3Harris Technologies, Inc. | 02/2021

This document does not contain technical data as defined by the ITAR 22CFR§120.10 or the EAR 15CFR§772. Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice at L3 Cincinnati Electronics Corporation, dba L3Harris Technologies' discretion. Call for latest revision. All brand and product names referenced are trademarks, registered trademarks, or trade names of their respective holders. Actual unit performance will depend on customer application.

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



L3HARRIS™
FAST. FORWARD.

1025 W. NASA Boulevard
Melbourne, FL 32919
t 800 852 5105 | f 513 573 6290
InfraredSales.cin@L3Harris.com