

SMALL TACTICAL TERMINAL (STT) KOR-24A

Link 16 and Secure VHF/UHF Line-of-Sight Networking at the Tactical Edge

The Small Tactical Terminal (STT) KOR-24A, co-developed by Viasat and L3Harris, is a two-channel radio designed to meet the needs of users who have size, weight and power constraints but need the information available on Link 16 networks and tactical VHF/UHF. Tactical warfighters, including ground vehicles, helicopters, UAVs, small boats and light ISR aircraft, can now have simultaneous access to Link 16 and either wideband UHF or legacy VHF/UHF. This terminal is packaged in an affordable, industry-standard compact form factor and is ruggedized to meet demanding environmental requirements.

PRODUCT DESCRIPTION

The STT brings real-time situational awareness, location data and command and control (C2) to tactical gateways and edge warfighters. With this terminal, edge users have access to both air and ground (friendly and enemy) situation data and can provide secure and reliable target data to the network. With the UHF channel configured for S-TADIL J or JRE, users have a single terminal that provides both LOS and BLOS TADIL J connectivity.

The STT can be used to bridge the gap in user's awareness between the air picture provided by TADIL J/Link 16 and the ground picture provided by other VHF/UHF data link formats. This two-channel radio dramatically reduces data latency and improves data integrity between traditional network platforms and users at the edge for both situational awareness and C2. Link 16 and combat net radio built-in identification means that STT terminals provide blue force reporting to reduce blue-on-blue engagements and avoid fratricide. With standardized TADIL messages and Ethernet interfaces, the STT can be used with multiple computers in a wide range of applications.

L3Harris is also the first Link 16 provider to integrate Concurrent Multinet (CMN) and Concurrent Contention Receive (CCR) advancements across its portfolio of Non-Developmental Items, providing warfighters with Concurrent Multiple Reception (CMR) capabilities for assured access to mission-critical information. These features, coupled with Link 16 Enhanced Throughput (ET) modes, will enable network planners to fully optimize network performance, allowing maximum participants sharing maximum capacity of information to support evolving mission requirements. The STT also implements the latest high assurance algorithms using a field proven programmable Cryptographic Modernization compliant engine to securely serve joint and coalition mission requirements, while maintaining backwards compatibility with legacy communications systems.



Simultaneous Two-Channel Comms for Air and Ground Interoperability

- > Link 16
- > Legacy VHF/UHF
- > Satcom
- > Wideband UHF
- SRW*
- ANW2*



Secure, Low SWaP
LOS Communications

MISSION FLEXIBILITY

- > Dual-channel radio
- > Link 16 and VHF/UHF waveforms
- > Voice and wideband data capable
- > Low size, weight and power
- > Lower acquisition costs
- > Multi-mission, multi-user and multi-waveform
- > Meets current and future requirements

SITUATIONAL AWARENESS

- > Friendly force tracking
- > Air and surface picture
- > Interfaces with:
 - L3Harris Link 16 toolset
 - Air Defense Systems Integrator (ADSI®)
 - Joint Range Extension (JRE)
 - TRAX
 - BOSS
 - CAYMAN
 - CDLIM
 - Gateway Manager
 - SPIDR

COMMAND AND CONTROL

- > J12 mission management to any non-C2
- > Status/weapons load/play times
- > WILCO/CANTCO

TARGET ATTACK

- > Shortens kill chain—F2T2EA (Find, Fix, Track, Target, Engage, Assess)
- > JTAC target POSID/9-line/BDA
- > Target update
- > Video, imagery and data
- > Mobile target attack

NSA CERTIFIED

SPECIFICATIONS AND TECHNICAL FEATURES

PERFORMANCE

- > Frequency Range: 30 to 512 MHz and 762 to 870 MHz narrowband VHF/UHF; 225 to 450 MHz wideband UHF; 969 to 1206 MHz Link 16
- > Transmission Modes: Simplex or half-duplex 16 kbps data, PT or CT; 1.25 MHz wideband UHF; Link 16 TDMA, All OP modes and enhanced throughput
- > Antenna Ports: VHF/UHF (2): 50 Ω ; Link 16 (2): 50 Ω
- > DC Power Input: 28 VDC per MIL-STD-704F; 3A Rx, <10A Tx
- > Configuration/Control/Data Interface: Ethernet 10/100 Base-T
- > Dimensions: 5" (w) x 5.6" (h) x 11" (d); 12.7 cm (w) x 14.2 cm (h) x 27.9 cm (d)
- > Weight: 16.5 lb; 7.5 kg
- > Crypto Modes: KY-57, ANDVT/KYV-5, KG-84C, KGR-96, KGV-8, KGV-11, CDH, KY-99, AES, and HAIPE®

RECEIVER

Adjacent Channel

- > Rejection: >40 dB
- > IF and image rejection: >65 dB

TRANSMITTER

- > Power Output: 250 mW to 5 W (VHF/UHF); 63 W (Link 16)

ENVIRONMENTAL

- > Operating Temperature: -40° C to +52° C with forced convection cooling; -30° C to +71° C with host platform ECS cooling; -40° to +60° C cold plate cooling
- > Storage Temperature: -54° C to +90° C
- > Relative Humidity: - \leq 90% non-condensing/MIL-STD-810F
- > Altitude: Operationally used above 80,000 ft
- > Shock: 52 G 30 msec all axes/MIL-STD-810F
- > Vibration: Jet: MIL-STD-810 Method 514.5 Category 24
Helo: MIL-STD-810 Method 514.5 Category 14

WAVEFORMS

- > VHF/UHF: VULOS, HAVE QUICK II, SINCGARS, voice and data
- > L-band: Link 16 data and voice including enhanced throughput modes

STANDARD FEATURES

- > Rugged, small and lightweight
- > SCA v2.2.2, reprogrammable embedded software
- > Advanced power management

- > VHF/UHF and Link 16 voice/data
- > Link 16 Frequency Remapping (FR)
- > Enhanced Throughput (ET)
- > Concurrent Multi-Net (CMN)
- > Concurrent Contention Receive (CCR)
- > Link 16 Crypto Modernization ready (software only update)
- > Crypto Modernized VHF/UHF
- > Modular design for easy growth
- > Integral VHF/UHF and L-band transmitter power amplifiers
- > VHF/UHF relay capability
- > Anti-jam waveforms
- > Interoperable with: JTIDS, MIDS-LVT, MIDS JTRS, VHF/UHF LOS with PRC-117, PRC-152, PRC-161, ARC-210,
- > Improved Data Modem (IDM)
- > Geodetic navigation
- > OMS compliant
- > L3Harris SA mode
- > 8.33 kHz Ch spacing

OPTIONAL FEATURES

- > External VHF/UHF PA
- > Mounting tray with fan
- > Power conditioning unit
- > ANW2C and SRW waveforms (Limited to Nations approved for each waveform)
- > HPW, HPW IP
- > DAMA, IW
- > P25

GROWTH CAPABILITIES

- > P25 Trunked
- > MIL-STD-188-220D
- > Link 16 Crypto Modernization Certified
- > Enhanced anti-jam



Small Tactical Terminal (STT) KOR-24A

© 2023 L3Harris Technologies, Inc. | 02/2023 | BCS | 22-DSD-282 | Rev-201

These item(s)/data have been reviewed in accordance with the International Traffic in Arms Regulations (ITAR), 22 CFR part 120.11, and the Export Administration Regulations (EAR), 15 CFR 734(3)(b)(3), and may be released without export restrictions.

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.

Use of U.S. DoD visual information does not imply or constitute DoD endorsement.



L3HARRIS®
FAST. FORWARD.

1025 W. NASA Boulevard
Melbourne, FL 32919
t 833 537 6837
CSW.Products@L3Harris.com