

## **VIDEOSCOUT®-CM3**

### **Rugged Communications Module Processing, Exploitation, Dissemination (PED) Management System**

The VideoScout-CM3 is an environmentally protected, semi-portable, remote video exploitation and management system designed for ground and maritime operations that provides the ability to control, receive, and process real-time video and metadata from ground and airborne surveillance platforms via a remotely mountable seven band antenna.

#### **PRODUCT DESCRIPTION**

VideoScout is a family of video processing, exploitation, dissemination (PED) management systems designed to capture, display, exploit, disseminate, and manage critical video intelligence from a variety of manned and unmanned sensors. The VideoScout-Communications Module, 3rd Generation further expands the VideoScout family of systems by providing users with an environmentally protected, semi-portable, remote video exploitation management system designed for ground and maritime operations; it can be mounted atop ship masts, surveillance towers, rooftops, vehicles or any other desired platform. The VideoScout-CM3 includes a secure L, S, C-Low and C-High band receiver and a UHF, L, S, C-Low, C-High, Ku-Low, and Ku-High band transceiver that supports any length of off-the-shelf coaxial antenna cable with a maximum insertion loss of up to 15 dB (approximately 100-500 feet, depending on cable type).

As the only system of its kind, the VideoScout-CM3 easily captures and leverages video and metadata from up to two Unmanned Aerial Systems (UAS), targeting pods, intelligence feeds, and other common sensors, as well as video from co-located perimeter security cameras. Users can deploy multiple VideoScout-CM3s in order to expand their field of coverage and control any number of systems via standard IP-based network protocol. This significantly traditional Line-of-Sight (LOS) coverage provides the end user with enhanced Situational Awareness (SA) across the area of operation.

The VideoScout-CM3 product is packaged with the VideoScout PED management software, VideoScout-Insyte®. With sufficient computer performance, this software enables users to capture 20+ simultaneous video feeds, each with its own 7-day Digital Video Recorder (DVR) buffer. It also supports data archiving along with immediate search, retrieval, exploitation and dissemination of captured video and/or associated imagery. VideoScout-Insyte is a Microsoft® Windows™-based applications, which facilitates easy integration into existing C4ISR systems and intelligence networks. This ability to easily exploit, manage, and disseminate data from multiple sources facilitates pre-mission planning, mission execution, and post-mission analysis. Users can pause, zoom, DVR, step back, and annotate video clips and images in near-real-time or on recorded video. This is achieved by recording voice from the user or external radios to support mission planning, execution, and post-mission analysis. Video and metadata are also stored and indexed automatically for subsequent search and retrieval. Warfighters can create geological smart video by synchronizing metadata with video by using applications such as FalconView® maps or Google Earth™ from within VideoScout-CM3 or via an Ethernet connection to Google Earth imagery.



Use of U.S. DoD visual information does not imply or constitute DoD endorsement.

### **Control, Receive, and Process Real-Time Video and Metadata**

#### **KEY FEATURES**

- > Ruggedized, portable communications module
- > Designed for ground and marine operations
- > Can be mounted atop ship masts, surveillance towers, rooftops, vehicles, or any other desired platform
- > Includes a secure L, S, C-Low and C-High band receiver
- > Includes a secure UHF, L, S, C-Low, C-High, Ku-Low, and Ku-High band transceiver



## SPECIFICATIONS

- > External interfaces: AES key fill (DS-101), antenna (x2), Ethernet (x2), Power Input, RS-170A (x2)
- > Size: 8" (w) x 10.5" (d) x 8.25" (h)
- > Weight: <28 lbs (excluding antennas)
- > Colors: Gray, tan, or green
- > Power: 8-265 VAC, 9-36 VDC, 95 Watts maximum
- > Video: H.264, H.265, MPEG-2, MPEG-4 Part 2, NTSC, PAL, RTSP
- > Humidity: MIL-STD-810G, Method 507.5, Proc II
- > Fungus: MIL-STD-810G, Method 508.6, Annex B
- > Dust: MIL-STD-810G, Method 510.5, Proc I
- > Vibration (operating): MIL-STD-810G, Method 514.6, Proc I, Cat 4
- > Vibration (storage): MIL-STD-810G, Method 514.6, Proc I, Cat 24
- > Vibration (shipboard): MIL-STD-165-1A, Type 1
- > Shock (functional): MIL-STD-810G, Method 516.6, Proc I, 40g, 11 ms
- > Shock (transit drop): MIL-STD-810G, Method 516.6, Proc IV
- > Shock (shipboard): MIL-S-901E, Grade A, Class I, Type A
- > Conducted emissions: MIL-STD-461G, CE101, CE102
- > Conducted susceptibility: MIL-STD-461G, CS101, CS114, CS115, CS116
- > Radiated emissions: MIL-STD-461G, RE101, RE102
- > Radiated susceptibility: MIL-STD-461G, RS103
- > Electrostatic discharge: MIL-STD-461G, CS118
- > Safety: IAW MIL-882 for system safety

## BANDS

- > UHF: 400 to 470 MHz<sup>2</sup>
- > L-Band: 1.65 to 1.85 GHz<sup>1,2</sup>
- > S-Band: 2.20 to 2.5 GHz<sup>1</sup>  
2.025 to 2.50 GHz<sup>2</sup>
- > C-Band: 4.40 to 5.0 GHz<sup>1,2</sup>  
5.25 to 5.85 GHz<sup>1,2</sup>
- > Ku-Band: 14.40 to 14.93 GHz<sup>2</sup>  
15.15 to 15.35 GHz<sup>2</sup>

## ENVIRONMENTAL

- > Altitude (storage): MIL-STD-810G, Method 500.5, Proc I, 40,000 ft
- > Altitude (operating): MIL-STD-810G, Method 500.5, Proc II, 15,000 ft
- > Temperature (storage): MIL-STD-810G, Method 501.5, 502.5, Proc I, -46C to +85C
- > Temperature (operating): MIL-STD-810G, Method 501.5, 502.5, Proc II, -40C to +65C
- > Temperature shock: MIL-STD-810G, Method 503.5, Proc 1-C, -46C to +85C
- > Rain: MIL-STD-810G, Method 506.5, Proc I

## TRANSCEIVER

WAVEFORM	ANALOG	BE-CDL A (0.512, 1, 2, 4, 8, 10, 16, 20 MBPS)		BE-CDL B MODES 101, 104 (0.2-44.736 MBPS)		CDL (0.2, 0.4, 2, 10.71A/B, 21.42, 44.73 MBPS)		DDL (2, 6 MBPS)		TACTICAL (0.466, 1.6, 3.2, 6.4 MBPS)	
Frequency Band	UHF	Rx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx				Rx
	L	Rx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx			Rx
	S	Rx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx			Rx
	C	Rx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx			Rx
	Ku	Rx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx/Tx	Rx			Rx
Encryption:			AES, Type 1	AES, Type 1	AES, Type 1	AES, Type 1	AES				AES

1. Receiver
2. Transceiver

## VideoScout-CM3 (PN: 575-72X5-002)

© 2023 L3Harris Technologies, Inc. | 08/2023 | BCS | 23-DSD-307 | Rev-201

This Datasheet consists of L3Harris technologies general capabilities information that does not contain technical data as defined within the International Traffic Arms Regulations (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11. Data, including specifications contained within this document are summary in nature and subject to change at any time without notice at L3Harris Technologies' discretion. All brand names and product names referenced are registered trademarks, or trade names of their respective holders. Use of U.S. DoD visual information does not imply or constitute DoD endorsement. DoD, OSR approved for public release Case No. 18-S-0782.

L3Harris Technologies is a Trusted Disruptor for the global aerospace and defense industry. With customers' mission-critical needs always in mind, our 46,000 employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains.

Use of U.S. DoD visual information does not imply or constitute DoD endorsement.



**L3HARRIS®**  
FAST. FORWARD.

1025 W. NASA Boulevard  
Melbourne, FL 32919  
t 833 537 6837  
CSW.Products@L3Harris.com