

XL ONBOARD™ SERIES

Ultra-Reliable, Road-Ready Radios



When your mission requires you to be mobile, you need a multiband radio that can move with you. Trust the XL Onboard™ series for the power and flexibility your work demands.

The ride is always smoother with a best-in-class radio by your side. The XL Onboard Series P25 radios bring unflinching critical communications to any vehicle in your fleet. Connect in ways others can't with either the multiband XL 200M or single-band XL 185M, both of which are FirstNet Ready®. XL Onboard radios offer LTE capability and include Wi-Fi® and Bluetooth® connectivity. Loud and clear audio with five speaker outputs paired with our advanced noise cancellation technology ensure you can hear and be heard in loud environments. The rugged, modular design combines the flexibility to fit any dashboard, with the fortitude to withstand tough conditions, while an intuitive interface frees your focus for the road ahead.

RELENTLESSLY RELIABLE

XL Radios run on systems that double down on redundancy, champion open networks and connect seamlessly with P25-compliant organizations.

POINT-TO-POINT SECURE

Our AES-256 encryption provides an end-to-end secure configuration, keeping you safe from threats.

BACKED WITH ALL-IN, 24/7 SUPPORT

Our service packages keep your radios up and running with in-field preventative maintenance and software upgrades.

Key Benefits

- > Interoperability across VHF, UHF, 700/800 and 900 MHz bands
- > Connects in more places with Wi-Fi, Bluetooth and GPS
- > The XL Onboard Series radios are AT&T® and Verizon® Certified
- > Both XL 200M and XL 185M are FirstNet Ready
- > Multiple encryption options for secure communications
- > Modular design for flexible mounting configurations
- > Field upgradeable LTE and broadband hotspot capabilities
- > Advanced noise cancellation technology
- > Ruggedized to MIL-STD-810G standards for tough conditions
- > 3.3-inch color display with 8 programmable buttons and simple menu access

SPECIFICATIONS FOR: XL ONBOARD SERIES

| GENERAL | | |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Dimensions (H x W x D): | | |
| Radio Only | 2.0 x 6.9 x 9.7 in (49 x 174 x 230.5 mm) | |
| Radio and Control Unit (includes knobs) | 2.4 x 6.9 x 12.8 in (60 x 175 x 320.7 mm) | |
| Control Unit (Remote) (includes knobs) | 2.4 x 6.9 x 4.0 in (60 x 175 x 72.2 mm) | |
| Weight: | | |
| Remote Mount Radio | 5.0 lbs (2.3 kg) | |
| Control Unit (Remote Mount) | 1.3 lbs (0.6 kg) | |
| Front Mount Radio with Control Unit | 7.0 lbs (3.2 kg) | |
| Channel/Talkgroup Capacity | 12,500 (1,250 per mission plan—up to 10 mission plans) | |
| Radio Programming | Firmware, personalities and feature set over Wi-Fi | |
| Control Unit | 18-bit color LCD 480 pixels x 220 pixels 3.3-inch color LCD with up to 3 lines of text 5 programmable favorites buttons Separate volume and channel selector knobs Built-in speaker Single DIN sizing 2 USB-C ports (1 for microphone) | |
| Speakers: | Two channels of 15 W of audio (< 3% distortion) on both the radio body and control head | |
| External, 15 W | | |
| Internal, 3 W | Built-in Control Head Speaker | |
| Environmental Specifications: | | |
| Relative Humidity | Per MIL-STD-810G | |
| Ambient Temperature Range ¹ | -22°F to +140°F (-30°C to 60°C) | |
| Altitude: | | |
| Operational | 15,000 ft (4,572 m) | |
| In-Transit | 50,000 ft (15,240 m) | |
| Electrical: | | |
| System Voltage | 10.8 to 16.6 VDC negative ground | |
| Standby Current Drain | 1 A | |
| Receive Current Drain | 2 A | |
| Current Drain @ 35W TX | 10 A | |
| Current Drain @ 50W TX | 15 A | |
| GPS/GNSS: | P25 standard tier 2 and L3Harris in-band | |
| | Without LTE Core Connectivity Module | With LTE Core Connectivity Module |
| Channels | 52 | 72 |
| GNSS Constellations Supported | 2 | 4 |
| Tracking Sensitivity | -165 dBm (GPS), -163 dBm (GLONASS) | -160 dBm (GPS & GLONASS) |
| Acquisition Sensitivity | -146 dBm (GPS) | -160 dBm (GPS & GLONASS) |
| Cold Start | < 35 seconds | 26 seconds |
| Hot Start | < 1 second | 1.5 seconds |
| Feature | | Accelerometer for location tracking / dead reckoning in GPS-challenged environments |

¹ For CCM equipped devices in the Australian and New Zealand markets, the recommended Ambient Temperature Range specification is -30°C to +45°C per the RCM directive for internal temperature limits for telecom equipment.

| LMR TRANSMITTER | | | | |
|----------------------------------|-------------------------------|--------------------------------------------------------|------------------------------------|--------------------|
| Frequency Bands (MHz) | VHF | UHF | 700/800 | 900 |
| Frequency Range (U.S.) | 136-174 | 378-522 | 768-776, 798-806, 806-816, 851-861 | 896-902, 935-944 |
| Frequency Range (Int'l) | 136-174 | 378-522 | 763-776, 793-806, 806-825, 851-870 | 896-902, 935-944 |
| Modulation Limiting (kHz) | 2.5, 5 (FM) | | | 5 (FM) |
| Audio Response | Meets TIA-603-D Section 3.2.6 | | | |
| Spurious and Harmonics (dBc) | < -75, FCC Part 90 | < -70, FCC Part 90 | < -75, FCC Part 90 | < -75, FCC Part 90 |
| FM Hum and Noise (dB @ 12.5 kHz) | 45.0 | | | |
| FM Hum and Noise (dB @ 25 kHz) | 47.0 | | | |
| Audio Distortion (%) | < 3.0 | | | |
| P25 Modulation Fidelity (%) | < 3.00 | | | |
| Frequency Stability (ppm) | ±1.5 | | | |
| P25 Adjacent Power (dB) | > 67 | > 67 @ 50 W (378-512 MHz) > 67 @ 25 W (512-522 MHz) | > 67 | > 67 |

SPECIFICATIONS FOR: XL ONBOARD SERIES

| LMR TRANSMITTER (continued from previous page) | | | | |
|------------------------------------------------|----------------------------|-----|-----|------|
| Channel Spacing (kHz) | 12.5, 25 | | | 12.5 |
| Conducted Emissions (dBc) | -75 | -70 | -75 | -75 |
| Radiated Emissions | Meets TIA/EIA-603-D 3.2.12 | | | |

| LMR RECEIVER | | | | |
|------------------------------------------------|-----------------------------------|---------|------------------|---------|
| Frequency Bands (MHz) | VHF | UHF | 700/800 | 900 |
| Frequency Range (U.S.) | 136-174 | 378-522 | 768-776, 851-861 | 935-944 |
| Frequency Range (Int'l) | 136-174 | 378-522 | 763-776, 851-870 | 935-944 |
| Channel Spacing (kHz) | 12.5, 25 | | | 12.5 |
| Sensitivity (12 dB SINAD) | -119 dBm | | | |
| P25 Sensitivity (5% BER) | -119 dBm | | | |
| Adjacent Channel Rejection @ 25 kHz (dB) | 77 | 78 | 76 | NA |
| Adjacent Channel Rejection @ 12.5 kHz (dB) | 72 | 70 | 70 | 70 |
| P25 Adjacent Channel Rejection @ 12.5 kHz (dB) | 60 | 60 | 60 | 60 |
| Intermodulation Distortion (dB) | 77 | 78 | 75 | 75 |
| FM Hum and Noise @ 12.5 kHz (dB) | 49 | 47 | 45 | 45 |
| FM Hum and Noise @ 25 kHz (dB) | 50 | 50 | 47 | NA |
| Rated Audio Output | 2 channels of 15 W RMS into 4 Ohm | | | |
| Audio Distortion | < 3.0% @ rated power | | | |
| Stability Rejection (ppm) | +/- 1.5 | | | |
| Spurious Rejection (dB) | 92 | 90 | 88 | 88 |
| Selectivity (dB) | NA | NA | 20 (NPSAC Only) | NA |

| BROADBAND | |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| LTE Protocol | 3GPP Release 11, Category 12, Power Class 3 UE with support for QoS QCI |
| North America LTE Option | FCC ID: N7NEM75S 4G LTE Bands: B2, B4, B5, B12, B13, B14, B17, B29*, B30*, B66 3G Bands: B2, B5 |
| International LTE Option (In selected countries) | 4G LTE Bands: B1, B3, B5, B7, B8, B28 3G Bands: B1, B5, B8 |
| Wi-Fi | 802.11ac 2.4 GHz; supports up to 10 client devices |
| Bluetooth | Bluetooth 4.0 (128-bit encryption) |

*Downlink only for Carrier Aggregation

| ENVIRONMENTAL STANDARD | | | |
|------------------------|---------------------|---------|----------------------|
| Applicable Standard | Parameter | Methods | Procedure/Categories |
| MIL-STD-810G* | Low Pressure | 500.5 | 1,2 |
| | High Temperature | 501.5 | 1,2 |
| | Low Temperature | 502.5 | 1,2 |
| | Temperature Shock | 503.5 | 1-B |
| | Solar Radiation | 505.5 | 1/A1 |
| | IP65 (Control Unit) | 506.5 | 1,3 |
| | IP54 (Radio) | 506.5 | 3 |

SPECIFICATIONS FOR: XL ONBOARD SERIES

| ENVIRONMENTAL STANDARD (continued from previous page) | | | |
|-------------------------------------------------------|----------------------------------|------------------------|--------------------------------------------|
| | Humidity | 507.5 | 2 |
| | Salt Fog | 509.5 | 1 |
| | Blowing Dust | 510.5 | 1,2 |
| | Vibration (Basic Transportation) | 514.6 | 1, Category 4 |
| | Vibration (Minimum Integrity) | 514.6 | 1, Category 24 |
| | Shock (Crash Hazard) | 516.6 | 5 |
| | Shock (Bench Handling) | 516.6 | 6 |
| U.S. Forest Service | Vibration (10-60 Hz) | Paragraph 2.15 | |
| IEC 60529 | Dust-tight and Water Jets | IP65 (Control Unit) | Table 2, Par. 13.4 Table 3, Par. 14.2.5 |

*Also meets equivalent superseded MIL-STD-810D, E and F

| DIGITAL OPERATION | | |
|------------------------------------|------------------------------------------------------------------------------------------------------|----------------------------|
| Protocol | P25 | ProVoice™ |
| Vocoding Method | AMBE+2™ Enhanced Full Rate & Enhanced Half Rate | AMBE+2™ Enhanced Full Rate |
| Signaling Rate (kbps) | 9.6 | 9.6 |
| Modulation | Phase 1 TX: C4FM, RX: C4FM & CQPSK Phase 2 TX: HCPM, RX: HDCQPSK | GFSK |
| L3Harris Failsoft Operation | Switch to site Trunking Mode (for L3Harris infrastructure) or P25 Conventional Failsoft for Motorola | |

| ENCRYPTION | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Encryption Algorithms | Voice Encryption: Single-key AES/DES, Multiple-key AES/DES, DES-OFB, Encryption Lite (ARC4), 256-bit AES P25, 64-bit DES Control Channel Encryption: 128-bit AES (LLA) |
| Encryption Keys Per Radio | Number of Encryption Keys per Keystore (up to 5 keystores per radio): 128 AES, 64 DES, 5 LLA, 8 Encryption Lite (ARC4), 4 AES UKEK, 4 DES UKEK |
| Keying | L3Harris Key Loader, P25 Over-the-Air-Rekeying (OTAR), Motorola KVL 3000+/4000/5000 |
| Standards | FIPS 140-2 Level 1, FIPS 197 |

| REGULATORY DATA | | | | | | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------|---------------------|--------------------|---------------------------------|
| Frequency Range | RF Output (W) | Frequency Stability | FCC Type Acceptance ID | Applicable FCC Rule | Industry Canada ID | Applicable Industry Canada Rule |
| 136-174 | 50.0 | | OWDTR-0161-E | 90 | 3636B-0161 | RSS-119 |
| 378-522 | 50.0 | | OWDTR-0161-E | 90 | 3636B-0161 | RSS-119 |
| 763-776, 793-806 | 30.0 | 0.1 | OWDTR-0161-E | 90 | 3636B-0161 | RSS-119 |
| 806-825, 851-870 | 35.0 | 0.1 | OWDTR-0161-E | 90 | 3636B-0161 | RSS-119 |
| 896-901 | 35.0 | 0.1 | OWDTR-0161-E | 90 | 3636B-0161 | RSS-119 |
| 935-944 | 35.0 | 0.1 | OWDTR-0161-E | 90, 101 | 3636B-0161 | RSS-119 |
| Emissions Designators | 16K0F3E, 16K0F1D, 16K0F1E, 14K0F3E, 14K0F1D, 14K0F1E, 11K0F3E, 11K7F1D, 11K7F1E, 7K10F1D, 7K10F1E, 8K40F1D, 8K40F1E, 8K10DXW, 18K5F1W, 12K9F1W | | | | | |

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

FirstNet and FirstNet Ready are registered trademarks and service marks of the First Responder Network Authority. All other trademarks belong to their respective owners.

XL Onboard 200M, XL Onboard 185M Single-Band Mobile Radio

© 2024 L3Harris Technologies, Inc. | 01/2024 SS022D

Non-Export Controlled Information

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our 50,000 employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. L3Harris.com.



1025 W. NASA Boulevard
Melbourne, FL 32919