

20 W GaN SSPA (MULTIBAND SOLID-STATE POWER AMPLIFIER)

Compact All-In-One L-, S- and C-Band Dual-Output SSPA

L3Harris multiband 20 W GaN SSPA is a dual-output digitally controlled power amplifier with four independent gallium nitride solid-state power amplifiers. It is capable of transmitting in L-Band, S-Band, Lower C-Band or Upper C-Band of the radio frequency (RF) spectrum. Our 20 W GaN SSPA is frequently used in targeting pod applications that require multi-frequency operation in rugged, SWaP-constrained environments.

PRODUCT DESCRIPTION

The 20 W GaN SSPA is a small, lightweight amplifier designed to be paired with multiband modems and radios—either stand-alone for a transmit-only system or integrated with additional components to form a duplex system. Our 20 W GaN SSPA amplifier is a multiband dual output solid-state power amplifier (SSPA) built using gallium nitride (GaN) technology. Our RF amplifier consists of a power supply, four independent solid-state power amplifiers and a digital control section. An RS-422 interface provides temperature monitor, RF output power level detect and VSWR fault status. The RS-422 interface also provides control of the band selection for RF power amplification and blanking capability of the RF signal. This multiband SSPA can select among and operate in L-Band, S-Band, Lower C-Band or Upper C-Band of the radio frequency (RF) spectrum. Our GaN multiband SSPA is designed for use with multiple L3Harris products.



All-In-One Compact Multiband Design

KEY FEATURES

- > Dual output of L-, S-, Lower C- or Upper C-Bands
- > Rugged, compact design
- > Low SWaP
- > Supports L3Harris CMDL, CMDL 2, VORTEX® and ROVER® 6

SPECIFICATIONS

PERFORMANCE CHARACTERISTICS

- > L-Band: 1.625 GHz to 1.85 GHz
 - Pout = +42.0 dBm min (ambient), +41.0 dBm min (hot)
- > S-Band: 2.20 GHz to 2.50 GHz
 - Pout = +41.0 dBm min (ambient), +40.0 dBm min (hot)
- > C-Band: 4.40 GHz to 4.94 GHz
 - Pout = +43.0 dBm min (ambient), +42.0 dBm min (hot)
- > C-Band: 5.25 GHz to 5.85 GHz
 - Pout = +42.3 dBm min (ambient), +41.3 dBm min (hot)

PHYSICAL CHARACTERISTICS

- > Size: 5.63" (l) x 4.88" (w) x 0.94" (h)
- > Weight: 1.6 lb.
- > Power
 - Input voltage: 26 VDC to 32 VDC
 - Power Consumption: 126 W (max) at 28 VDC

ENVIRONMENTAL CHARACTERISTICS

- > Operational Temperature: -40 °C to +75 °C (baseplate)
- > Non-Operational Temperature: -55 °C to +85 °C
- > Altitude (MSL): -500 ft. to 50,000 ft.
- > Vibration: 11.87 Grms, 5 Hz to 2000 Hz
- > Shock: 22 g, 11 ms sawtooth peak (MIL-STD-810F, Method 516.5 Proc. I)



Back View



Front View

20 W GaN SSPA (Multiband Solid-State Power Amplifier)

© 2025 L3Harris Technologies, Inc. | 09/2025 | BCS | 17-DSD-186 | Rev-202

NON-EXPORT CONTROLLED: THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit [L3Harris.com](https://www.l3harris.com) for more information.



1025 W. NASA Boulevard
Melbourne, FL 32919

[L3Harris.com](https://www.l3harris.com)