

# BANDIT™ 2x—MINIATURE TRI-BAND TRANSCEIVER

The new low-cost, lightweight, wideband data link and all-in-one digital transceiver with internal LNA and SSPA

The L3Harris BANDIT 2x Miniature L-, S- and C-Band Transceiver is a low-cost, lightweight, wideband data link and all-in-one digital transceiver adaptable to a wide variety of applications. The BANDIT 2x is the replacement to the widely deployed and successful L3Harris BANDIT line. With its new tri-band operation, increased output power, standard network interfaces and a built-in router, the BANDIT 2x is fully net-ready and is a powerful, tactical gateway into the net-centric battlespace.

# PRODUCT DESCRIPTION

The L3Harris BANDIT 2x tri-band transceiver is a small, lightweight and low-power digital transceiver that provides wideband data link capability adaptable to a wide variety of applications. It delivers real-time, IP-based, full-motion digital video for situational awareness, targeting, battle damage assessment, surveillance, video broadcast, remote sensors, convoy operations and other situations where high resolution video is required. The transceiver is designed primarily to be used on size and weight constrained platforms operating in harsh environments. It is interoperable with other products using L3Harris standard waveforms. The L-, S- or C-Band frequencies are centered around standard analog frequency ranges, making the BANDIT 2x software defined radio a perfect replacement for analog links adding better-performing digital signal transmission and improved security.





Low-cost, lightweight, wideband data link all-in-one digital transceiver

#### **KEY FEATURES**

- > Low cost and low SWaP
- Digital video and data routing and relay capability
- Symmetric digital data rates up to 42 Mbps
- > FIPS 197 AES encryption (available option)
- > Ethernet interfaces for imagery and data transmission
- > Small, ruggedized, all-in-one system—internal amplifier for each band
- > Configurable L- S- or C-Band operation for either transmit or receive
- Interoperable with a wide range of products that support commercial and proprietary waveforms
- > H.264 Video Encode (NTSC/PAL)

#### **SPECIFICATIONS**

#### PERFORMANCE CHARACTERISTICS

#### RF

> Transmit (TX) and Receive (RX) bands (simultaneously uses one band for TX and the other band for RX):

- L-Band: 1,350 MHz to

1,390 MHz, 1,755 MHz to 1,850 MHz, 1 KHz steps

- S-Band: 2,025 MHz to

2,500 MHz,

1 KHz steps

- C-Band Low: 4,400 MHz to

4,990 MHz, 1 KHz steps

# Encryption

> FIPS 197 AES1 (available option)

#### Waveforms

> IW (0.75, 1.5, 3.0, 6.0, 12.0, 24.0, and 42.0 Mbps)

# Networking

- > IPv4/IPv6
- > Layer 2 switching or Layer 3 routing
- > DHCP server

# External or User Interfaces

- > RS-232 (qty. 1)
- > 10/100 Base-T Ethernet (qty. 2)

# PHYSICAL CHARACTERISTICS SWaP

- > Size: 5.05" (l) x 2.85" (w) x 0.80" (h)
- > Weight: < 0.6 lb.
- > Power:
  - Input voltage: 10 to 30 VDC
  - Power consumption: 35 watts maximum
  - RF output power: ≥ 33 dBm in all bands

#### **Environmental**

- > Altitude: < 70,000 feet (design objective)
- > Temperature:
  - -40 °C to 55 °C, operating (forced air)
  - -55 °C to 85 °C, non-operating
- > Vibration: MIL-STD-810G (design objective)

#### **APPLICATIONS**

- > Group 1, 2 and 3 UAVs
- > Munitions
- > Smaller manned aircraft
- > Ground ISR/Command and Control platforms

			DIGITAL	
			International Waveform	FM Analog Tx
SUPPORTED FEATURES	Frequency Band	L	X	Х
		S	X	Х
		С	X	Х
	Encryption	AES <sup>1</sup>	X	



1 AES may be export controlled or restricted

© 2025 L3Harris Technologies, Inc. | 09/2025 | BCS | 18-DSD-197 | Rev-203

NON-EXPORT CONTROLLED: THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.



