

## MINI-T 2i (INTERNATIONAL) TRANSCIVER

Low SWaP, high data-rate modem meeting critical data link requirements for ground, air or shipboard configurations

The Mini-T 2i Transceiver is a small, network-ready, fully capable Common Data Link (CDL) terminal enhanced for wideband mobile networking. Configurable as either a surface or airborne terminal on-the-fly, the transceiver can be matched with a variety of antenna and power amplifiers for applications requiring wideband data throughput. The Mini-T 2i includes capabilities from its predecessor Mini-Ti, dual Gigabit Ethernet interfaces, HD video, X/Ku-band LOS and High Data Rate CDL up to 274 Mbps.

### PRODUCT DESCRIPTION

The L3Harris Mini-T 2i Transceiver provides low-cost, lightweight, wideband data link capabilities and is adaptable to a wide variety of applications. It delivers real-time, full-motion video for situational awareness, targeting, battle damage assessment, surveillance, convoy operations, and other situations where eyes-on-target are required. With standard network interfaces and a built-in wideband router, the Mini-T 2i is fully net-ready and is a powerful gateway into the net-centric battlespace. The Mini-T 2i transceiver provides enhanced air and ground coordination to shorten talk-on-target for time-critical operations. and delivers proven interoperability with fielded CDL and TCDL data links along with popular ROVER® products. Mini-T 2i transceiver is small, lightweight and rugged.



Mission Ready—Small,  
Interoperable, Wideband

### KEY FEATURES

- > Dual-band, full-duplex LOS capability
- > Symmetric and asymmetric data rates up to 274 Mbps
- > Mission selectable RFE and antenna; flexibility to meet system requirements
- > Supports both omnidirectional and directional antenna systems
- > Control GUI including router configuration, pre-mission configuration and video display
- > MPEG-2, H.264, 1080p HD video
- > Applications
  - Manned ISR aircraft
  - Mobile-systems
  - Ground-based Tactical Operations Center (TOC)

## SPECIFICATIONS

### LOS PERFORMANCE CHARACTERISTICS

#### Transmit and Receive Bands

- > X-band:
  - 9.75 GHz to 10.44 GHz
- > Ku-band:
  - 14.40 GHz to 15.35 GHz

#### Data Rates

- > CDL/STANAG 7085: 200 kbps to 274 Mbps
- > Other Non-CDL data rates available
- > BE-CDL Rev B: Up to 274 Mbps

#### Encryption Options

- > AES

#### External

- > Networking
- > Layer 2, 3 switching/routing
- > Supports OSPF, RIP and others
- > Supports multi-cast
- > 802.1Q VLANs
- > NAT available at 45 Mbps and below
- > DHCP server/client

#### External or User Interfaces

- > User I/O:
  - Ethernet (Qty 2; Gig Ethernet)
  - RS-232 (Qty 2; Console, GPS)
  - RS-422
  - Audio (Full-duplex CDL voice)
  - USB 2.0
- > Sensor Interface Options:
  - RS-170 (NTSC and PAL), HD-SDI
  - MPEG-2, H.264, HD 1080p encode and decode

- > Antenna, RFE I/O:
  - Ethernet (Qty 1; 10/100)
  - RS-232 (GPS)
  - RS-485 (antenna control)
  - Omni or directional antenna
- > Other:
  - RF in (X and Ku)
  - RF out (X and Ku)
  - $10^{-8}$  bit error rate (at range limit)

### PHYSICAL CHARACTERISTICS

#### SWaP

- > Size: 14.2 cm (w) x 6.1 cm (h) x 24.1 cm (l)  
5.6" (w) x 2.4" (h) x 9.5" (l)
- > Weight: 2.5 kg (5.5 lb.)
- > Power: 85 watts at +28 VDC

#### Environmental

- > Temperature:
  - Operating: -40 °C to +60 °C (46 CFM)
  - Non-Operating: -40 °C to +85 °C
- > Altitude: -154 m to 21,336 m (-500 ft. to 70,000 ft.)
- > Humidity: 0 to 100%, condensing
- > Shock: 20 G, 11 msec (terminal sawtooth peak)
- > Vibration: MIL-STD-810F, method 514.5
- > EMI: MIL-STD-461E
- > Salt Fog: MIL-STD-810F
- > Fungus: MIL-STD-810F

#### Mini-T 2i (International) Transceiver

© 2025 L3Harris Technologies, Inc. | 10/2025 | BCS | 17-DSD-154 | Rev-203

**NON-EXPORT CONTROLLED:** THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit [L3Harris.com](https://www.l3harris.com) for more information.



1025 W. NASA Boulevard  
Melbourne, FL 32919

[L3Harris.com](https://www.l3harris.com)