

FALCON III® RF-7850S SPR™

Advanced wideband Secure Personal Radio (SPR)

The L3Harris Falcon III RF-7850S SPR provides the ultimate integration of radio, edge device, GPS and application software in a single, compact and lightweight platform.



Equipped with the unique L3Harris Soldier-TDMA Networking Waveform (S-TNW), the radio delivers team-based voice, fully networked platoon-wide communication and reliable position reports, ensuring every soldier stays connected. It provides both wideband and narrowband operation modes and meets specific needs of soldier-level communications with multiple talk groups, ad-hoc mesh networking and multi-hop forwarding.

Engineered to meet the challenges of today's digital battlefield, the RF-7850S SPR's simple, robust web-based user

interface can be viewed with a supported web browser on any edge device. Because it comes with the easy-to-use L3Harris Ground Force Tracker, battle-management systems capabilities are in the hands of every soldier, whatever device is used. This allows soldiers to download maps and see the location of all soldiers on the network.

The RF-7850S SPR is interoperable with legacy L3Harris SPR and Falcon III radio families. Plus, its software-defined radio (SDR) architecture supports simplified in-field configuration and upgrades to new capabilities.



**POWERFUL
CONNECTIVITY FOR
EVERY SOLDIER**

KEY BENEFITS

- Equipped with Type 3 ANW2®C standard and long range modes – increasing wideband interoperability, range and mission flexibility
- Long-range, wideband interoperability and high-speed IP-networked data and Full Motion Video (FMV) provides enhanced situational awareness and tactical ISR
- Ultimate integration of radio, edge device, GPS and application software in a single platform
- Every soldier stays connected with unique soldier-specific waveform delivering wideband and narrowband operation
- Enhanced sharing of intelligence with multiple talk groups, ad-hoc mesh networking and multi-hop forwarding
- Battle-management systems capability brought to soldier level through L3Harris Ground Force Tracker
- Primed for Soldier Systems integration with both L3Harris and commercial off-the-shelf (COTS) devices

GENERAL	
RT Nomenclature	RF-7850S
Frequency Range	ANW2C* TGW2 and S-TNW 225-2500 MHz LOS/FSK 225-512 MHz TNW 25K & 75K 225-511.975 MHz
Channel Spacing/Bandwidth	Wideband modes: 500, 1.2 MHz, 5 MHz Narrowband mode: 25 kHz Channel spacing: 25 kHz
Net Presets	13
GPS	Built-in GPS with automatic position reporting
Management Tool	Communication Planning Application (RF-7850SH-CD001)
Frequency Tuning	10 Hz
Frequency Stability	± 1.0 ppm
Alerts	Audible status, optional foreign language prompts
Voice Operations	Full duplex audio Multiple, concurrent talk-groups Push-To-Talk (PTT) operation Stereo audio capable Selectable PTT activation

MODES AND WAVEFORMS	
Video TDMA Networking Waveform (V-TNW*)	Advanced Warfighter Video Waveform: Offers video streaming capability at the tactical edge Optimized to support multiple video streams to provide battlefield SA and intelligence Supports up to two talk groups if needed to confirm video intelligence
ANW2C*	Supports both 1.2 and 5 MHz bandwidths
Vanguard™ and Vapor™*	Enhanced, resilient tactical edge waveforms that deliver hopping capability along with high-speed IP data
Voice and Data Modes	MELPe and CVSD Voice
Telephony	Embedded SIP

PHYSICAL	
Dimensions	~ 8.3 H x 3.1 W x 2 D in (21.0 H x 8.0 W x 5.0 D cm) with standard battery
Weight	< 1.8 lbs. (0.81 kg) w/battery
Volume	Approx. 475 cc
Color	Green/Black/Tan CARC paint

ENVIRONMENTAL	
Temperature	-22°F to +131°F (-30°C to +55°C)
Immersion	2 meters for 30 minutes
Shock and Vibration	Ground portable
Sand/Dust/Salt/Fog/Rain	MIL-STD-810G, test methods 510.5, 509.5 and 506.5
Humidity	MIL-STD-810G, test method 507.5

INTERFACES	
Data	USB 2.0, IP over USB, RS232
Audio	9-pin SPR Fischer connector for stereo audio and multiple PTT control
Antenna Port	TNC connector
Function Knob	16-position knob
Remote Control	ASCII and Web API optional
Wireless Personal Area Network (WPAN optional)	Embedded Wi-Fi, Bluetooth, Low Energy
Embedded Applications	Web User Interface with built-in Ground Force Tracker, compatible with standard internet browsers
GPS Antenna Port	SMA female connector

STANDARD KIT	
12121-2730-01 (225-450 MHz, 1250-1390 MHz, and 1755-1850 MHz)	Tri-band antenna
12041-2400-0X	Rechargeable battery
10515-0474-4100	Field reference guide

See L3Harris Product Catalog for accessories

*Optional add-on

MODES AND WAVEFORMS	
Narrowband Waveforms	TDMA Networking Waveform: Narrowband communication mode Optimized voice and guaranteed GPS reporting Frequency hopping (ECCM) operation TNW 25 and TNW 75 VHF-UHF Line-Of-Sight: Narrowband communication mode Interoperable with L3Harris radio systems
Talk Group Wideband Waveform (TGW2)	TDMA-based advanced wideband communication (TGW2) for team-level deployments Simultaneous voice and data, up to 240 kbps Frequency 225 MHz to 2.5 GHz

Falcon III® RF-7850S SPR™

© 2025 L3Harris Technologies, Inc. | 12/2025 | L31122

NON-EXPORT CONTROLLED: THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit L3Harris.com for more information.



1025 W. NASA Boulevard
Melbourne, FL 32919

L3Harris.com