

RF-9820S

Compact Team Radio

The RF-9820S Compact Team Radio delivers robust voice and data capabilities for missions on the move. This multi-mission solution gives warfighters the flexibility of tactical MANET and legacy line-of-sight (LOS) capabilities in a Small Form Factor (SFF).

The RF-9820S features a simplified user interface, allowing radio operation with minimal training time. Secure, reliable communications in contested and congested environments is supported with in-field upgrades to emerging wideband and narrowband resilient waveforms.

The Compact Team Radio is compatible with L3Harris AN/PRC-163 Multi-channel Handheld accessories and battery, reducing logistics support and allowing for easy kit-swapping among radios. MIL-STD ruggedized to withstand harsh conditions, this handheld is also SWaP-optimized to reduce warfighter burden.

The RF-9820S ensures connectivity with ground-based tactical teams by supporting multiple modes of operation, including wideband MANET and narrowband voice and Position Location Information (PLI).



COMPACT, EASY-TO-USE, MULTI-MISSION SOLUTION

KEY BENEFITS

- > Robust voice and data for missions on the move
- > Resilient communications in contested and congested environments
- > Simplified operation and compatibility with AN/PRC-163 batteries and accessories
- > Versatile operational modes include tactical MANET and legacy LOS

GENERAL	
RF-Romenclature	RF-9820S
Frequency Range	225 - 2600 MHz (waveform dependent)
Net Presets	99
Channel Spacing/Bandwidth	25 kHz - 20 MHz
GPS	Internal GPS
Management Tool	Windows®-based Communications Planning Application (CPA); WebMMI for network monitoring and management TrellisWare™ Management Tool*
Frequency Tuning	10 Hz

PHYSICAL	
Dimensions	3.8 H x 3.1 W x 1.7 D in (without battery) 9.6 H x 7.8 W x 4.3 D cm (without battery)
Volume (without battery)	18 in ³ (295 cc)
Weight (without battery)	1 lbs (450 g)

TRANSMITTER	
Power Output	3.2 watts
Spurious Suppression	Per TIA-603D
Harmonic Suppression	Per TIA-603D

RECEIVER	
Sensitivity	-116 dBm, 12 dB SINAD
Adjacent Channel Rejection	Per TIA-603D
Squelch	Noise, Tone, CTCSS or CDCSS

POWER	
Power Input	9 V to 17 VDC
Battery Type	Rechargeable lithium-ion battery

OPTIONAL MODES AND WAVEFORMS	
Narrowband Waveforms	UHF Line of Sight (ULOS) Katana™ ARROW 1.1
Wideband Waveforms	Wraith™ TSM™ 6.1* TSM 6.3 (HDR+)*
Voice and Data Modes	Voice Analog CVSD MELPe GSM-AMR 5.9 Data Wideband up to 50 Mbps

ENVIRONMENTAL	
Temperature	Operating: -22°F to 131°F (-30°C to +55°C) Storage: -40°F to 158°F (-40°C to 70°C)
Immersion	2 meters
Shock and Vibration	MIL-STD-810H
Sand/Dust/Salt/Fog/Rain	MIL-STD-810H
EMI/RFI	MIL-STD-461G

INTERFACES	
Data	USB 2.0, IP over USB and ethernet
Audio	19-pin ADF, Audio, USB 2.0, fill
Antenna Port	50-Ohm TNC
Programming	USB 2.0
Function Knob	OFF, 1-13 presets, F, Z
Remote Control	WebMMI, SoftKDU

*TrellisWare and TSM and TSM-X are registered trademarks of TrellisWare Technologies, Inc. in the United States and other countries.

RF-9820S

© 2026 L3Harris Technologies, Inc. | 03/2026 | L32196

NON-EXPORT CONTROLLED: THIS DOCUMENT CONSISTS OF INFORMATION THAT IS NOT DEFINED AS CONTROLLED TECHNICAL DATA UNDER ITAR PART 120.33 OR TECHNOLOGY UNDER EAR PART 772.

L3Harris is the Trusted Disruptor in defense tech. With customers' mission-critical needs always in mind, our employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security. Visit [L3Harris.com](https://www.l3harris.com) for more information.



1025 W. NASA Boulevard
Melbourne, FL 32919

[L3Harris.com](https://www.l3harris.com)